

# Series "VERSUZ"


**MODEL:** VERSUZ LED / 1200mm / SURFACE,SUSPENDED / 19W / 2195lm / CRI>80RA / CCT 4000K / ECG / IP54 / OPAL HIGH DIFFUSIVE / ANODIZED ALUMINUM

**CODE:** VerS/P.120-19-2195/10.4/IP54O5A

**LED LIGHT SOURCE**

*Mareli Ltd*  
www.mareli-bg.com

## STANDARD



on request

## DESCRIPTION

### MOUNTING

Surface / Suspended

### LIGHT SOURCE

LED

### OPTICAL SYSTEM

Diffuser

### MATERIALS

Housing - Anodised aluminium profile

Diffuser - Opal PMMA high diffusive

End caps - Anodised aluminium

### WIRING

Input Voltage: 170-240VAC 50-60Hz

Ambient Temp: -10~35 °C

Supplied with white cable (3x0.5mm<sup>2</sup> L=600mm)

### LIGHT DISTRIBUTION

Direct


### SURFACE FINISH

Housing & End caps - anodised aluminium

### ADVANTAGES

- Net lumen output 2195 lm
- Color rendering index >80 Ra
- CCT 4000K
- Durable and Long service life
- No Infrared radiation
- No UV rays
- 50,000 hrs lifetime
- 5 years warranty

Areas of application



### ACCESSORIES

Single suspender 1.5 m (ORDER CODE: ACSus/VerP 1/1.5)

Transparent Feeding Cable for Versuz Surface and Suspended

3 X 0.75mm<sup>2</sup>. VDE certified cable L=1m ( the length of the cable can be different ) (ORDER CODE: AC/TC/Ver 3/1\*)



energy saving



eco friendly



maintenance free




UV/IR no UV/IR rays



5 years warranty

## VerS/P.120-19-2195/10.4/IP54O5A

|             |                             |
|-------------|-----------------------------|
| <b>Ver</b>  | Versuz - Name of luminaire  |
| <b>S/P</b>  | Surface, Suspended mounting |
| <b>120</b>  | 1200mm Length               |
| <b>19</b>   | Power (W)                   |
| <b>2195</b> | Net lumen output            |
| <b>10.4</b> | 10.4 = CCT: 4000K           |
| <b>IP54</b> | Ingress protection          |
| <b>O5</b>   | Opal PMMA high diffusive    |
| <b>A</b>    | Anodised housing            |



| CODE                            | OPTICAL SYSTEM          | POWER | LIGHT SOURCE | NET LUMEN OUTPUT | COLOR RENDERING INDEX | COLOR TEMPERATURE | DIMENSIONS | WEIGHT |
|---------------------------------|-------------------------|-------|--------------|------------------|-----------------------|-------------------|------------|--------|
|                                 | DIFFUSER                | (W)   |              | (lm)             | (Ra)                  | (K)               | (mm)       | (kg)   |
|                                 | OPALPMMA HIGH DIFFUSIVE |       |              |                  |                       |                   |            |        |
| VerS/P.120-19-2195/10.4/IP54O5A | +                       | 19    | LED          | 2195             | >80                   | 4000              | L: 1162    | 0.62   |